



FORESTPRO90

9' LOG LOADER FORESTRY TRAILER

(FOR ATV AND UTV)



Remote control optional

9' LOG LOADER, TRAILER, ADJUSTABLE HYDRAULIC TANDEM AXLE, WINCH AND POWER UNIT

- FEATURES

- Grapple maximum opening 30"
- Grapple minimum closed 3"
- Tires 26-12-12
- Adjustable hydraulic tandem axle 20"
- Power unit 7 HP
- Hydraulic winch 4000 lbs (1/4" x 85' cable)
- · Boom length 9'
- Grapple continuous rotation
- Lift capacity at full extension 500 lbs
- Load capacity on axle 10 000 lbs
- Hydraulic stabilizing arms
- 6" adjustable pull bar
- Cylinder protected by relief valve
- Re-inforced frame built with oblique structural steel
- · Hydraulic control «joystick» type
- Baked powder paint



PRO90WH

Lenght	Width	Height	Approx. Weight
12′	55″	55″	1 000 lbs

OPTIONS	Details
G12	Bucket 12"
TVSF6	Auger 6"
BG90	Hydraulic dumping box
TELEC	Remote control for winch

ALSO AVAILABLE	Details	
GS90/95	Grapple o	only
RS90/95/110	Rotator o	nly



9'6" LOG LOADER FORESTRY TRAILER

(FOR ATV AND UTV)

9'6" LOG LOADER, TRAILER, ADJUSTABLE HYDRAULIC TANDEM AXLE. WINCH AND POWER UNIT



- FEATURES

- Grapple maximum opening 30"
- Grapple minimum closed 3"
- Tires 26-12-12 or 11 L 15
- Adjustable hydraulic tandem axle 20"
- · Boom length 9'6"
- Grapple continuous rotation
- Lift capacity at full extension 700 lbs
- Load capacity on axle 10 000 lbs
- Hydraulic stabilizing arms
- 8" adjustable pull bar
- Cylinder protected by relief valve
- Re-inforced frame built with oblique structural steel
- · Hydraulic control «joystick» type
- Baked powder paint

- PRO95WH (model inclusion)

- Power unit 7 HP
- Hydraulic winch 4000 lbs (1/4" x 85' cable)



PRO95WH

Lenght	Width	Height	Approx. Weight
14'1"	63"	68"	1550 lbs

OPTIONS	Details	
TR4	Hydraulic winch 4000 lbs (1/4" x 85' cable)	
7 HP	Power unit 7 HP	
G12	Bucket 12"	
G20	Bucket 20"	
TVSF6	Auger 6"	
BG95	Hydraulic dumping box	
TELEC	Remote control for winch	

ALSO AVAILABLE	Details	
PRO95	9'6" log loader, trailer and adjustable hydraulic tandem axle, 1 450 lbs	
PRO95W	9'6" log loader, trailer, adjustable hydraulic tandem axle and winch, 1 500 lbs	
CS95 Log loader only (grapple, support plate with bolts rotator included)		
GS90/95	Grapple only	
RS90/95/110	Rotator only	

FORESTPRO110

11' LOG LOADER **FORESTRY TRAILER**

(FOR TRACTOR)

11' LOG LOADER, TRAILER, ADJUSTABLE MANUAL TANDEM, WINCH AND POWER UNIT



- FEATURES

- Grapple maximum opening 36"
- Grapple minimum closed 4"
- Tires 12 L 15 12 ply
- Adjustable manual tandem
- · Boom length 11'
- Grapple continuous rotation
- Lift capacity at full extension 900 lbs
- Load capacity on axle 20 000 lbs
- · Hydraulic stabilizing arms
- Cylinder protected by relief valve
- Re-inforced frame built with oblique structural steel
- · Hydraulic control «joystick» type
- Baked powder paint

PRO110WH

Lenght

15'6"

- PRO110WH (model inclusion)

Width

67"

- Power unit 7 HP
- Hydraulic winch 4000 lbs (1/4" x 85' cable)



Remote control optional

OPTIONS	Details
TR4	Hydraulic winch 4000 lbs (1/4" x 85' cable)
7 HP	Power unit 7 HP
G12	Bucket 12"
G20	Bucket 20"
TVSF6	Auger 6"
PNHW	Agricultural tires «highway» service 12,5 L
BG110	Hydraulic dumping box
TELEC	Remote control for winch

Height

68"

ALSO AVAILABLE	Details	
PRO110	11' log loader, trailer and adjustable manual tandem, 1750 lbs	
PRO110W	11' log loader, trailer, adjustable manual tandem and winch, 1 800 lbs	
CS110	Log loader only (grapple, support plate with bolts and rotator included)	
GS110	Grapple only	
RS90/95/110	Rotator only	

FORESTPRO140

14' LOG LOADER FORESTRY TRAILER

(FOR TRACTOR)

14' LOG LOADER, TRAILER, ADJUSTABLE MANUAL TANDEM. WINCH AND POWER UNIT



- FEATURES

- Grapple maximum opening 36"
- Grapple minimum closed 4"
- Tires 12 L 15 12 ply
- Adjustable manual tandem
- Boom length 14'
- Grapple continuous rotation
- Lift capacity at full extension 1100 lbs
- Load capacity on axle 20 000 lbs
- · Hydraulic stabilizing arms
- Cylinder protected by relief valve
- Re-inforced frame built with oblique structural steel
- · Hydraulic control «joystick» type
- Baked powder paint

- PRO140WH (model inclusion)

- Power unit 14 HP
- Hydraulic winch 5000 lbs (3/8" x 100' cable)



PRO9140WH

Lenght	Width	Height	Approx. Weight
18'6"	68"	89"	2 700 lbs

OPTIONS	Details	
TR5	Hydraulic winch 5000 lbs (3/8" x 100' cable)	
14 HP	Power unit 14 HP with electric starter	
TVSF6	Auger 6"	
PNHW	Agricultural tires «highway» service 12.5 L 15	
BG140	Hydraulic dumping box	
TELEC	Remote control for winch	

ALSO AVAILABLE	Details	
PRO140	14' log loader, trailer and adjustable manual tandem, 2 400 lbs	
PRO140W	14' log loader, trailer, adjustable manual tandem and winch, 2 600 lbs	
CS140	Log loader only (grapple and rotator included)	
GS140	Grapple only	
RS140	Rotator only	





CONTINUOUS WRAPPER MODEL

(ROUND BALE)

THE QUICKEST AND SIMPLEST BALE EJECTOR SYSTEM ON THE MARKET. MAINTENANCE FREE.

- FEATURES

- Continuous round bale wrapper from 4' to 5' length and from 4' to 5'6" diameter
- 2 aluminium stretchers 30"
- 14 HP power unit with electric starter
- 18 amps alternator
- Raise and lower front axle hydraulically
- Bale compaction adjustable hydraulically by brake system on wheels
- · Direct drive (hydraulic)
- · Front wheel drive with traction tires
- Hydraulic tailgate
- Manual hydraulic control «joystick» type
- For freight: length 14'8" / width 8'6" / height 9'4"
- Machine goes from 9'6" working mode to 8'6" transportation mode quickly and easily
- · Baked powder paint

PERFORMANCE

- Wrapping performance of 120 bales per hour
- Bale counter
- Plastic wrap shortage detector
- Plastic wrap stops on the bale, «NOT» on the joint
- Hermetic and uniform wrapping made possible by our hydraulic brake system and the ability to double the wrapping automatically on the joints

- REMOTE CONTROL OR «DIRECT»

- · Steering by remote control or direct
- Start and stop the motor by remote control or direct
- Eject bales by remote control or direct
- Double the plastic wrapping by remote control
- Securely restart the automatic system by remote control

- LIGHTS AND SECURITY

- Working lights
- · Road lights
- · Safety light to indicate that the engine is running
- · Advanced security protection for users
- Security guards
- Emergency stop on the machine or by remote

ADVANTAGES

- Use 40% less plastic than an individual wrapper
- More standard caracteristics than our competitors



PROLINER

Working dimension		Approx. Weight	
Lenght	Width	Height	
18′	10′	9'4"	3 700 lbs

Remote control included





CONTINUOUS WRAPPER HYBRID MODEL

(ROUND AND SQUARE BALE)

THE QUICKEST AND SIMPLEST BALE EJECTOR SYSTEM ON THE MARKET AND WITHOUT MAINTENANCE.

-FEATURES

- \bullet Continuous round bale wrapper from 4' to 5' length and from 4' to 5'6" diameter and square bale from 3' to 4' by 6' in length
- 4 aluminium stretchers 30"
- 14 HP power unit with electric starter
- 18 amps alternator
- Raise and lower front axle hydraulically
- Bale compaction adjustable hydraulically by brake system on wheels
- Direct drive (hydraulic)
- · Front wheel drive with traction tires
- · Hydraulic tailgate
- · Manual hydraulic control «joystick» type
- For freight: length 15' / width 8'6" / height 9'8"
- Machine goes from 9'6" working mode to 8'6" transportation mode quickly and easily

- PERFORMANCE

- Wrapping performance of 120 bales per hour
- Bale counter
- Plastic wrap shortage detector
- Plastic wrap stop on the bale «NOT» on the joint
- Hermetic and uniform wrapping made possible by our hydraulic brake system and the ability to double the wrapping automatically on the joint

- REMOTE CONTROL OR «DIRECT»

- Steering by remote control or direct
- Start and stop the motor by remote control or direct
- Eject bales by remote control or direct
- Double the plastic wrapping by remote control
- Securely restart the automatic system by remote control

- LIGHTS AND SECURITY

- Working lights
- · Road lights
- · Safety light to indicate that the engine is running
- Advanced security protection for users
- · Security guards
- Emergency stop on the machine or by remote

ADVANTAGES

- Use 40% less plastic than an individual wrapper
- More standard caracteristics than our competitors





ALLLINER

Working dimension			Approx. Weight
Lenght	Width	Height	4 500 lbs
20′	10′	9'8"	

Pictures shown might have some options.

TWISTERIOO

INDIVIDUAL WRAPPER MODEL

(ROUND BALE)

-FEATURES

- Individual round bale wrapper from 4' to 5' diameter
- Manual hydraulic wrapping
- Hydraulic plastic cutting system
- 1 aluminium stretcher 30"
- Allows the bale to dropped close to the ground
- Bale counter and turn counter
- Manual hydraulic control «joystick» type
- Baked powder paint



ADVANTAGES

- Quick wrapping
- Easy to transport
- Low maintenance cost
- Proven technology
- Allows to be used in the field as well as on-site
- Lightweight and compact

TW100			
Lenght	Width	Height	Approx. Weight
11′8″	74"	77"	1100 lbs

OPTION	Details	
14 HP	Hydraulic power unit including 14 HP - 14 HP power unit with electric starter - Motor with 18 amps alternator	



